



TECHNICAL DATA SHEET

KEIM GEWEBE-ECKWINKEL-PLUS

1. PRODUCT DESCRIPTION

Corner angle with glass-fibre fabric, wide plastic legs and stable trailing edge.

2. FIELD OF APPLICATION

Especially for use on building edges in the AquaROYAL and Klassik-Plus system.

3. PRODUCT PROPERTIES

- easy and fast processing
- for interior and exterior use
- universally applicable
- non-slip
- alkali-resistant
- resistant to aging

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Check the adhesion of the insulation panels after at least 3 days. Insulation panels that are not bonded or damaged must be replaced. The glued and if necessary dowelled insulation panels must be dry, free of dust, clean and level.

CONSUMPTION:

approx. 1,1 m/m

APPLICATION:

Apply the system's reinforcing mortar at the appropriate points and embed KEIM Gewebe-Eckwinkel-Plus centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

5. PACKAGING

Product name	Mesh size	Length [m]	Pieces per unit	Content per sold unit [m]	Type of container	Length
Gewebe-Eckwinkel-Plus 6x6	6 x 6 mm	2.50	25	62.5	carton	

Delivery in cartons

6. STORAGE

Storage conditions
flat-lying in the outer cardboard avoid deflection dry frost-free

7. DISPOSAL

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de