



TECHNICAL DATA SHEET

KEIM PUTZABSCHLUSSPROFIL

1. PRODUCT DESCRIPTION

Render separation profile made of high-quality plastic with fixed fabric flag and plaster removal edge in various projections.

2. FIELD OF APPLICATION

For exact separation of different plaster coatings.

Putzabschlussprofil 3 mm for 3 mm plaster application

Putzabschlussprofil 6 mm for 6 mm plaster application

Putzabschlussprofil 8 mm for 8 mm plaster application

Putzabschlussprofil 10 mm for 10 mm plaster application

Putzabschlussprofil 20 mm for 20 mm plaster application

3. PRODUCT PROPERTIES

- suitable for all insulation panel thicknesses and kinds
- easy to use
- fire behaviour: hardly inflammable B1 according to 4102
- non-slip
- long-lasting
- highly weather-resistant

4. APPLICATION INSTRUCTIONS

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be in the range between max. 5 °C and max. 30 °C.

CONSUMPTION:

approx. 1,1 m/m

APPLICATION:

KEIM Putzabschlussprofil is to be applied before the application of the base coat.

The Putzabschlussprofil 20 mm may also be used to form field boundary joints. The arrangement of field boundary joints must be determined by a specialist planner.

REINFORCEMENT:

Apply the system's reinforcing mortar at the appropriate points and embed KEIM Putzabschlussprofil centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

AFTERTREATMENT:

After complete drying of the base coat, the surface is reinforced.

TECHNICAL DATA SHEET – KEIM PUTZABSCHLUSSPROFIL

5. PACKAGING

Product name	Projection	Length [m]	Pieces per unit	Content per sold unit [m]	Type of container	Length
Putzabschlussprofil 3 mm	3 mm	2.50	25	62.50	carton	
Putzabschlussprofil 6 mm	6 mm	2.50	25	62.50	carton	
Putzabschlussprofil 8 mm	8 mm	2.50	25	62.50	carton	
Putzabschlussprofil 10 mm	10 mm	2.50	25	62.50	carton	
Putzabschlussprofil 20 mm	20 mm	2.50	25	62.50	carton	

Delivery in cartons

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering flat-lying in the outer cardboard

7. DISPOSAL

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de