



## TECHNISCHES MERKBLATT

# SOCKELDÄMMPLATTE-WEISS 035

## 1. PRODUCT DESCRIPTION

---

Weißer EPS-Hartschaum nach DIN EN 13163.

## 2. FIELD OF APPLICATION

---

Sockeldämmplatte in Spritzwasser-belasteten Bereichen, auch in Kombination mit KEIM WDV-Systemen.

Allgemein bauaufsichtlich zugelassen für: exterior walls; window and door reveals

Anwendungstyp nach DIN 4108-10 WAS.

Geeignet für: Masonry or concrete, rendered and unrendered; panel material in timber construction; building sealing; ETICS upgrade system

Nicht geeignet für: cold self-adhesive plastic membrances; horizontal and inclined surfaces exposed to weathering; metallic substrates.

## 3. PRODUCT PROPERTIES

---

- easy to use
- good heat insulation
- HBCD-free (with new flame retardant)
- free of CFC, CHC and aromatic hydrocarbons
- fire behaviour: hardly inflammable B1 according to 4102
- resistant to aging
- resistant to splashing water and moisture
- The insulation panels comply with the high standards of the VDPM e.V. (association for insulation systems, renders and mortars)
- Externally monitored by Forschungsinstitut für Wärmeschutz e.V. München

### MATERIAL CHARACTERISTICS:

- |  |               |
|--|---------------|
| - Rated value of thermal conductivity: | 0,035 W/mK    |
| - Panel size:                          | 1000 x 500 mm |
| - Panel thickness:                     | 20 und 30 mm  |
| - Edge formation:                      | dull          |
| - Colour shade:                        | white         |

## 4. APPLICATION INSTRUCTIONS

---

### APPLICATION:

Cut to size with insulation knife or hot wire cutter.

### 5. PACKAGING / TECHNICAL DATA

---

Panel thickness [mm]	edge	m <sup>2</sup> per bundle	Pieces per unit
20*	dull	12.00	24
30*	dull	8.00	16

\* Lieferung bundweise nur als Beiladung zu mindestens einer weiteren Palette Dämmplatten

### 6. STORAGE

---

max. storage time	Storage conditions
no maximum storage time	dry protected from heat and direct sun.

### 7. DISPOSAL

---

#### EC WASTE CODE:

Waste code: 17 06 04



KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood / Telford / Shropshire TF2 7NA  
Tel. +44 1952 231 250 / Fax +44 1952 231 251  
www.keim.com / sales@keimpaints.co.uk