

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: KEIM I.G.PRIMER (I&F-GRUND)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Priming
- · Uses advised against All other uses are not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood GB-Telford, Shropshire TF2 7NA Tel +44 1952 231 250 / Fax +44 1952 231 251

www.keim.com / sales@keimpaints.co.uk

· Further information obtainable from:

David Pratt

Telefon: +44 1952 231250
E-Mail: sales@keimpaints.co.uk
• 1.4 Emergency telephone number:
GBK GmbH Global Regulatory Compliance
Emergency number: +49(0)6132/84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2-methylpropan-1-ol ethyl acetate propan-2-ol n-butyl acetate

(Contd. on page 2)



Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P315 Get immediate medical advice/attention.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with regional/national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicablevPvB: Not applicable

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Preparation based on synthetic resins and organic solvents

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥25-<50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25- XXXX	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	_ ≥10-<20%

(Contd. on page 3)



Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

CAS: 123-86-4	n-butyl acetate	Contd. of page 2)
EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29- XXXX	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
CAS: 78-83-1	2-methylpropan-1-ol	≥3-<10%
EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23- XXXX	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 64-17-5	ethanol	≥2.5-<10%
EINECS: 200-578-6 Index number: 603-002-00-5	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	≥2.5-<10%
EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29- XXXX	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
CAS: 6846-50-0	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	≥1-<2.5%
EINECS: 229-934-9	& Repr. 2, H361; Aquatic Chronic 3, H412	1

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

With appearance of symptoms or in cases of doubt seek medical advice .

In case of unconsciousness place patient stably in side position for transportation.

When seeing the doctor we suggest to present this safety data sheet.

Immediately remove any clothing soiled by the product.

After inhalation:

Take affected people into fresh air and keep quiet.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not use solvents or thinners.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse mouth and throat well with water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, thick, black smoke develops. Inhalation of the dangerous decomposition products may cause serious health damages.

In case of fire, the following can be released:

carbon oxide (COx)

Nitrogen oxides (NOx)

- 5.3 Advice for firefighters
- · Specila protective equipment: Wear self-contained respiratory protective device.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

In case of fire do not breathe smoke, fumes and vapours.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Do not inhale fumes.

Respect the protection rules (see section 7 a. 8).

Wear protective equipment. Keep unprotected people away.

6.2 Environmental precautions:

Do not allow product to reach soil, sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Follow local governmental rules and regulations.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Absorb with non-combustible liquid-binding material (sand, earth, diatomite, vermiculite).

Ensure adequate ventilation.

Dispose of the material collected according to regulations.

Clear contaminated areas thoroughly.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Page 5/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

See Section 13 for disposal information.

(Contd. of page 4)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Do not inhale aerosols.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Avoid contact with skin and eyes.

See item 8 (8.2) for information about suitable protective equipment and technical precautions. Respect the protection rules.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Use explosion-proof apparatus / fittings and spark-proof tools.

Use only in explosion protected area.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Keep in the original containers in a cool and dry place.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store under lock and key and out of the reach of children.

Store receptacle in a well ventilated area.

Protect from frost.

Please note information on label

Keep container tightly sealed.

Protect from heat and direct sunlight.

Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

(Contd. on page 6)



Page 6/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

	(Contd. of page 5
67-63-	0 propan-2-ol
	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm
123-86	6-4 n-butyl acetate
	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
78-83-	1 2-methylpropan-1-ol
	Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm
64-17-	5 ethanol
WEL	Long-term value: 1920 mg/m³, 1000 ppm
108-65	5-6 2-methoxy-1-methylethyl acetate
	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale aerosols.

· Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Combination filter A

· Protection of hands:

After each cleaning use treatment creams, for very dry skin greasy ointments.

Protective gloves

· Material of gloves

suitable material e.g.:

Butyl rubber, BR

Recommended thickness of the material: > 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: level \geq 6 (480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 6)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

if applicable face protection

· Body protection:

Solvent resistant protective clothing

After contact with skin wash thoroughly with water and apply lotion.

· Limitation and supervision of exposure into the environment

See Section 12 and 6.2

No further relevant information available.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Solvent-like
Odour threshold: Not determined

· pH-value: Not determined

· Change in condition

Decomposition temperature:

Melting point/freezing point: Not determined

Initial boiling point and boiling range: >35 °C

· Flash point: <7 °C

· Flammability (solid, gas): Not applicable

· Ignition temperature: Not determined

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, the formation of

Not determined

explosive air/vapour mixtures is possible.

· Explosion limits:

Lower: 0.6 Vol %
Upper: 15 Vol %
Oxidising properties: Not applicable

Vapour pressure at 50 °C: <1,100 hPa

Density at 20 °C: 0.9* g/cm³

· Relative density Not determined

(Contd. on page 8)



Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

	(Contd. of page 7
· Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Partly soluble.
Partition coefficient: n-octanol/water:	Not applicable
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	18 s (DIN 53211/4)
Solvent separation test:	<3 % (20°C)
9.2 Other information	* The values are for freshly produced material and may change with the time.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal conditions of storage and use.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Bases

oxidizing agents

Acids

· 10.6 Hazardous decomposition products:

In case of fire, the following can be released:

Carbon oxides (COx)

Nitrogen oxides (NOx)

No hazardous decomposition products if stored and handled as prescribed.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Frequent persistent contact with the skin may cause skin irritation.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Causes serious eye damage.

(Contd. on page 9)



Page 9/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 8)

· during inhalation:

Vapours may cause drowsiness and dizziness.

Irritant effect possible.

- during swallowing: Irritant effect possible
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Other information (about experimental toxicology):

Experimental analysis are not available.

The product was not tested. The statements on toxicology have been derived from the properties of the individual components.

- · Subacute to chronic toxicity:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Not applicable
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · AOX-indication:

According to our standard of knowledge the product does not contain any organic bounded halogen. The product has no influence on the waste water's AOX-value.

According to the formulation contains the following heavy metals and compounds from the EU guideline NO. 2006/11/EC:

According to our current data base the product does not consist of any heavy metals or substances of EU-directives 76/464/EWG.

· General notes:

Do not allow product to reach ground water, water course or sewage system.

At present there are no ecotoxicological assessments.

The statements on ecotoxicology have been derived from the properties of the individual components.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable · **vPvB:** Not applicable

(Contd. on page 10)



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 9)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

• ADR 1263 PAINT, special provision 640D

· **IMDG**, **IATA** PAINT

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33

· EMS Number: F-E,S-E

· Stowage Category B

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	(Contd. of page 1
· Transport/Additional information:	The applicable
· ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
Exospida quantitios (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 m
Transport category	2
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 n
UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

For information on labelling please refer to section 2 of this document.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations
- · Please note:

TRGS 200 (Germany)

TRGS 500 (Germany)

TRGS 510 (Germany)

TRGS 900 (Germany)

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 14.0 Revision: 08.02.2021

Trade name: KEIM I.G.PRIMER (I&F-GRUND)

(Contd. of page 11)

- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: KEIMFARBEN Germany, Product safety department

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

EC10: Effective concentration at 10% mortality rate.

EC50: Half maximal effective concentration.

LC10: Lethal concentration at 10% mortality rate.

NOEC: No observed effect concentration.

REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.